



ER60 PRO

FROM **CEMB** EXPERIENCE

ER60 PRO balancer is the result of CEMB consolidated experience in the manufacturing of high technology garage and industrial balancers since 1946. Development and cooperation with the most important car and tyre manufacturers guarantee to the professionals in the garage equipment field:

- Reliability
- Easy and quick use
- Accuracy
- 3D measures
- Reduced cycle time!

CORE OF TECHNOLOGY

- Automatic gauge to measure the distance and diameter of rims of up to 28" with an innovative clip to hold the adhesive weight
- Virtual Sonar for 3D measurements of wheels that, in cases of metal rims and absence of sonar, calculates the width of the rim
- AutoAdaptive Mode The new tolerance calculation system
- **Electromagnetic brake** for the lock of the wheel in the exact weight position
- Laser indicator for inside weight positioning
- Software programs for the professionals: SPLIT, OPT, ALU
- **ALU-S3D Balancing mode** Adhesive weights on the internal rim planes with specific counterweight position indicator
- VDD Virtual Direct Drive Very quick and maintenance free measurement system CEMB PATENT

ErGoFast line

- With ER60 PRO, CEMB widens its range of products ERG0FAST, maintaining the concepts of ergonomics and practicality together with the original design
- WBA Wheel Best Access
 Wide space to work inside the rim
- Digital multifunction display
- Ergonomic tool positioning CLOSE AT HAND!
- Laser indicator



Innovative clip to hold the adhesive weight









Virtual Sonar

INNOVATIVE 3D SOFTWARE THAT CAI CUI ATES RIM WIDTH

- After acquiring the position of the first plane of correction, the new software Virtual Sonar calculates the width of the rim, identifying a possible range of external correction planes.
- During the measurement spin, Virtual Sonar verifies that it is possible to fall within the tolerance with the correction indicated on all possible external planes.
- If there is even one possible plane for which the required correction does not allow the residual unbalance to fall within the tolerance range (calculated with AutoAdaptive software), the machine will request manual entry of the rim width in mm.





AutoAdaptive Mode THE NEW TOLERANCE CALCULATION SYSTEM

The innovative tolerance calculation system AutoAdaptive Mode is based on the evaluation of the residual imbalance limit value corresponding to an acceptable perceived vibration. For each wheel that is balanced, the software AutoAdaptive Mode detects weight and dimensions and calculates the tolerance value that will cancel any vibration perceived on the steering wheel. AutoAdaptive Mode grants the highest comfort when driving and saves balancing time.

In 1952 Cemb created the cone adapters for balancing machines and since then the company continued developing and producing high precision centering systems for any type of wheel. Cemb does not recommend the use of non-original adapters on its balancing machines.

STANDARD ACCESSORIES

UC20/GLM40 41FF034431

Standard equipment composed of: 3 cones Ø 45÷110 mm, quick locknut with handwheel GLM40, pincer-hammer and 60 g counterweight.



Standard equipment composed of: 3 cones Ø 45÷110 mm, quick locknut GL40, pincer-hammer and 60 g counterweight.





OPTIONAL ACCESSORIES - Especially designed for car manufacturers



RL CUP 41FF79255

Large plastic cup with polyurethane protection ring for light alloy rims.

UH20/2 41FF42048

Universal adapter for all wheels with 3,4,5,6 holes (pitch circle Ø 95-210 mm) complete with high precision back centering double cone (Cemb patent) for wheels with/without central hole (Renault, Peugeot and Citroën). Grants double accuracy compared to similar adapters on the market.

PEUGEOT-CITROËN KIT 41FF73171

High precision kit composed of: 1 bush \emptyset 60mm + 2 cones (\emptyset 62 \div 68 mm and \emptyset 54 \div 60 mm). Developed according to Peugeot and Citroën specifications.

VL/2 CONE + G36 DISC 41FF86174

Kit for light truck wheels (Ø 97÷170mm central hole).

SR4 - SR5 - SR5/2 - SRUSA

Stud adapters for rim protection and high precision centering for wheels with 4 or 5 holes. Studs are made of two pieces, elastically coupled: pressure is therefore homogeneous on all the holes.

RENAULT KIT 41FF77152

High precision kit composed of: 5 bushes (\emptyset 60 / 66 / 71 / 88 / 129,9 mm). Developed according to Renault specifications.

MT CONE 40FF57321

High precision graduated cone for German cars (with central hole \emptyset 56,5 / 57 / 66,5 / 72,5 mm).


MERCEDES KIT 41FF88003

High precision kit composed of: 3 cones (Ø 57- Ø 66,5 - Ø 84/85mm) + 1 pressure spring, according to Mercedes Benz specifications.

FOR MORE INFORMATION SEE THE COMPLETE BROCHURE ON THE WEB SITE:

www.cemb.com





Single	nhase	nower	ylqque
JIIIUIU	pilast	DOMPI	JUDDIA

B 4		
IVIAX	absorbed	nower

Balancing speed

Measuring cycle for 15 kg (33 lb) wheel

Measurement uncertainty

Avarage noise

Rim width setting range

Rim diameter setting range

Max. wheel weight

Machine weight

115 / 230 V 50/60 Hz

0,15 kW

100 rpm

4.7 s

1 g

< 70 dB (A)

 $1.5" \div 20" \, / \, 40 \div 510 \; mm$

 $10" \div 30" / 265 \div 765 \text{ mm}$

< 75 kg


120 kg





Zero Weight Lift

OPTION TO REDUCE ANY EFFORT



For more information see the complete brochure on the web site ${\bf www.cemb.com}$

Wheel loading and removal without effort or adjustment

PERFECT CENTERING

Wheel automatic lifting Ideal centering and more accurate balancing

QUICK

Quicker than any other traditional lift
A single pedal controls the whole working cycle

AUTOMATIC

Electronic system with PLC

UNIVERSAL

Applicable to any CEMB balancing machine



CEMB S.p.A.

Via Risorgimento, 9 23826 Mandello del Lario (LC) - Italy





Garage equipment division CEMB - ITALY Plant and Training Center Phone +39 0341 706111 garage@cemb.com

CEMB USA - BL Systems Inc.

2873 Ramsey Road Gainesville, GA 30501 - USA Phone +001 678 717 1050 Fax +001 678 717 1056 sales@cemb-usa.com